


Laserliner®

MultiMeter-Compact



Compact universal multimeter with all functions for professionals

Rev. 0612



- Fast and precise **voltage, current, resistance, capacitance, frequency and duty factor measurement**
- **Automatic range changeover and manual range preselection**
- **Automatic continuity tester** with acoustic signal
- **Diode test function** for determining integrity and polarity
- **Integrated contactless voltage indicator** with acoustic, visual and vibration warning
- **High measurement resolution** for precisely determining different measurement variables
- **Data HOLD function** for measuring in inaccessible places
- **CAT III - 1000 V** – can be used for measurements throughout building installations
- Large, easy-to-read **LC display with back-lighting**
- **Compact, impact-resistant enclosure with base support and selector switch**

TECHNICAL DATA

MAX. INPUT VOLTAGE	1000 V AC/DC
VOLTAGE RANGE	V/DC: 0...600 V, ± 0.5% V/AC: 0...600 V, ± 1.2%
CURRENT RANGE	A/DC: 0...10A, ± 2.5% A/AC: 0...10A, ± 3.0%
RESISTANCE RANGE	0...20 Mohm, ± 0.8%
CAPACITANCE RANGE	0...100 µF, ± 3.0%
FREQUENCY RANGE	0...10MHz, ± 1.5%
DUTY FACTOR RANGE	0.1...99.9 %, ± 1.2%
CONTINUITY TEST	Resistance range <1.2 kohm
DIODE TEST	0.3 mA ±10%
PROTECTION CLASS	II, double insulation
OVERVOLTAGE CATEGORY	CAT III - 1000 V / CAT IV - 600 V Pollution degree 2
LC-DISPLAY	0...3999
POWER SUPPLY	1x 9V battery (NEDA 1604, IEC 6F22)
DIMENSIONS	150 x 70 x 48 mm
WEIGHT	255g



Large, illuminated display

Easy-to-use function knob

Vibration alarm

ARTICLE	ARTICLE NO.	EAN CODE	PU
MultiMeter-Compact	083.034A	4 021563 671236	5



MultiMeter Compact
+ 2 test prods
+ batteries

Package size (W x H x D)
190 x 310 x 75 mm