

Стълба алуминиева двураменна комбинирана

Марка: STS



EN 131



| Šifra/Code/Chi ffre/Шифр B1 0B2 | /230 | /250 | /280 | /300 |
|--|------|------|------|-------|
| Gazilata/Rungo/Sprossen/Сунгас | 2x8 | 2x9 | 2x10 | 2x11 |
| • A zatvorena/retracted/eingeschoben/закръпий (mm) | 2260 | 2520 | 2790 | 3080 |
| • B otvorena/open/ausgeschoben/Открытые (mm) | 2010 | 2230 | 2480 | 2780 |
| • C produžena/extended/verlänger/продолженелье (mm) | 3385 | 3925 | 4475 | 5045 |
| • C1 radna visina/working height/arbeitshöhe/рабочая высот (mm) | 3056 | 3564 | 4080 | 4615 |
| Max. vanjaka širina/Max. external width/Max. außenbreitena/Мак. внешняя ширин (mm) | 460 | 460 | 460 | 460 |
| Težina/Weight/Gewicht/Вес (kg) | 7,80 | 8,10 | 9,00 | 11,60 |
| Stabilizator/Stabilizer/Stabilisator/Стабилизатор (mm) | 764 | 764 | 894 | 894 |








Combination ladder two sections